## **RONDA<sup>®</sup>** Vacuum Cleaner



#### **TECHNICAL DATA**

By-pass motor	1200	W
By pace motor	230	V
	230	v
Data of the installed motor:		
- Vacuum, max. (per motor)	2450	mmWc
, u ,	24	kPa
- Airflow	58	l/sec.
- AILIOW		
	209	m³/h
Noise level (ISO 11201)	<70	dB(A)
* Suction power, max.		( )
((P2) based on IEC 60312)	285	W
Collection capacity (bag**)	35	1
Height	1000	mm
Width	575	
		mm
Length/depth	590	mm
Weight without accessories	33	kg
Container coupling	ø 50	mm
Length of supply cable	8	m
Collection capacity, liquid	15	1
Head, pump	3	m
	12	
Amount of water, pump	IZ	l/min.
* D ( () () () () () () () () () () () () (		
* Data of the vacuum cleaner with 4 m ø 38 mm hose ** Depending on the material		
		/

### Model 370

### 80.26.2541

RONDA<sup>®</sup> 370 is a small, mobile recycling system especially developed for cooling water supply in connection with diamond drilling, grinding and sawing. The effective cleaning system of the machine purifies the concrete sludge and ensures a continuous recycling of the cooling water. At the same time the machine can be used as a wet cleaner for the collection of liquids and sludge.

In many countries the authorities require that no concrete sludge is let out into the sewerage or the surroundings. RONDA<sup>®</sup> 370 collects the concrete sludge directly at the place of work. The sludge is filtered out of the water, and the clear water will be pumped back to the concrete tool, where it is reused as cooling water.

RONDA<sup>®</sup> 370 is filled with water or connected to the water supply. The level control ensures a constant liquid level and ensures enough liquid for the cooling of the concrete tool. As the machine recycles the water, refilling will only be necessary to a limited extent. This means both saving of water and a smaller environmental impact.

The machine is very compact and easy to manoeuvre, which means that it can easily be brought along, also to the fifth floor.

- Integrated cooling water pump for tools for diamond drilling, grinding and small sawing tasks
- Special filter bag for the filtering of the concrete sludge
- Float to protect against entry of liquid into the motor
- Strong trolley frame
- Low noise level
- Handy, compact and easy to manoeuvre

## V.BRØNDUM







### STANDARD ACCESSORIES:

- 2 Clear plastic hose, 4 m...... 84.54.0013
- 3 Synthetic bag, 5 bags/packet ...... 82.64.0061





### **OPTIONAL EXTRAS:**

### **MACHINE VARIANT:**

# **V.BRØNDUM**<sup>∉</sup>

Sadolinsvej 14 DK-8600 Silkeborg Tel. +45 86 82 43 66 Fax +45 86 80 33 63